

SLANGF 4 10-3 50-4 90°.JS87P

Produkt
 Tube
 4.10
 x3.50-
 4
 Tube
 Size:
 4.10
 x3.50-
 4
 Tube
 Size
 4.10
 x3.50-
 4
 Stem
 Angle
 Type
 90



degrees-90° JS87P When installed, stem is parallel with the edge of the rim Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high-low temperatures Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

STENS produktbeskrivelse:

- Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes
- Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high/low temperatures
- Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications
- Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification
- When installed, stem is parallel with the edge of the rim
- 90 degrees/JS87P
- 4.10x3.50-4

StensDimensjoner

Varegruppe	Tube
Antall pr. artikkel	1 stk
Vekt	0.2086524902 Kg
Inkludert i	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

Tilleggsinfo	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire
Delenummer konkurrenter	12201 22292 223-4145 71-275 B1320020 T354-P TS662
Cross Sell	165-015, 160-309, 165-021, 160-662, 160-003, 160-609, 160-300, 160-605, 160-633, 165-163, 160-344, 160-340
Up Sell	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire
Produsentens merkevare	Stens
GTIN-nummer	023899010226
Relatert produkt	160-003
OEM-nummer	Carlisle: 320020
Produsentinformasjon	Bruk med 160-003 Tire
Lengde	177.0 mm
Høyde	70.0 mm
Bredde	130.0 mm
Vekt	0.21 kg

Les mer om produktet her:

<https://www.ariens.no/product?number=170-005>