

## SLANGF 4 10-3 50-4 90°.JS87P

Produkt  
 Tube  
 4.10  
 x3.50-  
 4  
 Tube  
 Size:  
 4.10  
 x3.50-  
 4  
 Tube  
 Size  
 4.10  
 x3.50-  
 4  
 Stem  
 Angle  
 Type  
 90



degrees-90° JS87P When installed, stem is parallel with the edge of the rim. Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification. Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications. Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high-low temperatures. Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes. Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

### STENS produktbeskrivelse:

- Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes
- Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high/low temperatures
- Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications
- Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification
- When installed, stem is parallel with the edge of the rim
- 90 degrees/JS87P
- 4.10x3.50-4

### StensDimensjoner

Varegruppe	Tube
Antall pr. artikkel	1 stk
Vekt	0.2086524902 Kg
Inkludert i	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

<b>Tilleggsinfo</b>	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire
<b>Delenummer konkurrenter</b>	12201 22292 223-4145 71-275 B1320020 T354-P TS662
<b>Cross Sell</b>	165-015, 160-309, 165-021, 160-662, 160-003, 160-609, 160-300, 160-605, 160-633, 165-163, 160-344, 160-340
<b>Up Sell</b>	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire
<b>Produsentens merkevare</b>	Stens
<b>GTIN-nummer</b>	023899010226
<b>Relatert produkt</b>	160-003
<b>OEM-nummer</b>	Carlisle: 320020
<b>Produsentinformasjon</b>	Bruk med 160-003 Tire
<b>Lengde</b>	177.0 mm
<b>Høyde</b>	70.0 mm
<b>Bredde</b>	130.0 mm
<b>Vekt</b>	0.21 kg

Les mer om produktet her:

<https://www.ariens.no/product?number=170-005>