

TURF

Tube



23x10.50-12 ; 26x12.00-12 Tube Size: 23x10.50-12 (26x12.00-12) Stem Angle Type Straight-TR13 Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high-low temperatures Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes Use with 165-788 Tire 165-788 Tire, Use with 165-404 Tire 165-404 Tire, Use with 160-429 Tire 160-429 Tire, Use with 165-524 Tire 165-524 Tire, Use with 165-575 Tire 165-575 Tire, Use with 160-437 Tire 160-437 Tire, Use with 165-800 Tire 165-800 Tire, Use with 165-052 Tire 165-052 Tire, Use with 165-160 Tire 165-160 Tire, Use with 165-204 Tire 165-204 Tire, Use with 165-618 Tire 165-618 Tire, Use with 165-560 Tire 165-560 Tire, Use with 165-270 Tire 165-270 Tire, Use with 165-120 Tire 165-120 Tire, Use with 165-400 Tire 165-400 Tire, Use with 165-159 Tire 165-159 Tire, Use with 160-433 Tire 160-433 Tire, Use with 165-512 Tire 165-512 Tire, Use with 165-526 Tire 165-526 Tire

STENS produktbeskrivelse:

- Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes
- Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high/low temperatures
- Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications
- Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification
- Straight/TR13
- 23x10.50-12 (26x12.00-12)

StensDimensjoner

Varegruppe	Tube
Antall pr. artikkel	1 stk
Vekt	1.7077752730500002 Kg
Inkludert i	Use with 165-788 Tire 165-788 Tire, Use with 165-404 Tire 165-404 Tire, Use with 160-429 Tire 160-429 Tire, Use with 165-524 Tire 165-524 Tire, Use with 165-575 Tire 165-575 Tire, Use with 160-437 Tire 160-437 Tire, Use with 165-800

Tire 165-800 Tire, Use with 165-052 Tire 165-052 Tire, Use with 165-160 Tire 165-160 Tire, Use with 165-204 Tire 165-204 Tire, Use with 165-618 Tire 165-618 Tire, Use with 165-560 Tire 165-560 Tire, Use with 165-270 Tire 165-270 Tire, Use with 165-120 Tire 165-120 Tire, Use with 165-400 Tire 165-400 Tire, Use with 165-159 Tire 165-159 Tire, Use with 160-433 Tire 160-433 Tire, Use with 165-512 Tire 165-512 Tire, Use with 165-526 Tire 165-526 Tire

Tilleggsinfo	Use with 165-788 Tire 165-788 Tire, Use with 165-404 Tire 165-404 Tire, Use with 160-429 Tire 160-429 Tire, Use with 165-524 Tire 165-524 Tire, Use with 165-575 Tire 165-575 Tire, Use with 160-437 Tire 160-437 Tire, Use with 165-800 Tire 165-800 Tire, Use with 165-052 Tire 165-052 Tire, Use with 165-160 Tire 165-160 Tire, Use with 165-204 Tire 165-204 Tire, Use with 165-618 Tire 165-618 Tire, Use with 165-560 Tire 165-560 Tire, Use with 165-270 Tire 165-270 Tire, Use with 165-120 Tire 165-120 Tire, Use with 165-400 Tire 165-400 Tire, Use with 165-159 Tire 165-159 Tire, Use with 160-433 Tire 160-433 Tire, Use with 165-512 Tire 165-512 Tire, Use with 165-526 Tire 165-526 Tire
Delenummer konkurrenter	10959 22316 223-2310 3264 7-08757 71-283 71-408 7400561 B1321050 BHA126 T1012 TU012 TU-2385 TU-2412
Cross Sell	165-788, 165-404, 160-429, 165-524, 165-575, 160-437, 165-800, 165-052, 165-160, 165-204, 165-618, 165-560, 165-270, 165-120, 165-400, 165-159, 160-433, 165-512, 165-526
Up Sell	Use with 165-788 Tire 165-788 Tire, Use with 165-404 Tire 165-404 Tire, Use with 160-429 Tire 160-429 Tire, Use with 165-524 Tire 165-524 Tire, Use with 165-575 Tire 165-575 Tire, Use with 160-437 Tire 160-437 Tire, Use with 165-800 Tire 165-800 Tire, Use with 165-052 Tire 165-052 Tire, Use with 165-160 Tire 165-160 Tire, Use with 165-204 Tire 165-204 Tire, Use with 165-618 Tire 165-618 Tire, Use with 165-560 Tire 165-560 Tire, Use with 165-270 Tire 165-270 Tire, Use with 165-120 Tire 165-120 Tire, Use with 165-400 Tire 165-400 Tire, Use with 165-159 Tire 165-159 Tire, Use with 160-433 Tire 160-433 Tire, Use with 165-512 Tire 165-512 Tire, Use with 165-526 Tire 165-526 Tire
Produsentens merkevare	Stens
GTIN-nummer	023899010462
Relatert produkt	160-429
OEM-nummer	Carlisle: 321050
Produsentinformasjon	Bruk med 160-429 Tire
Lengde	328.0 mm
Høyde	135.0 mm
Bredde	174.0 mm
Vekt	1.71 kg

Les mer om produktet her:

<https://www.ariens.no/product?number=170-126>