

## SLANGF 410-3 50-4 RFTT

Produkt  
 Type  
 4.10  
 x3.50-  
 4  
 Tube  
 Size:  
 4.10  
 x3.50-  
 4  
 Tube  
 Size  
 4.10  
 x3.50-  
 4  
 Stem  
 Angle  
 Type



Straight-TR13  
 Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification  
 Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications  
 Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high-low temperatures  
 Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes  
 Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

### STENS produktbeskrivelse:

- Advanced extrusion technology ensures consistency and eliminates thin walling problems common with other tubes
- Higher percentage of butyl rubber for greater elasticity, insulation, air tightness and resistant to high/low temperatures
- Individually pre-aired and inspected utilizing advanced technology to ensure conformance to JIS (Japanese Industrial Standards) specifications
- Manufactured by one of the world's largest tube manufacturers under ISO 9001 certification
- Straight/TR13
- 4.10x3.50-4

### StensDimensjoner

Varegruppe	Tube
Antall pr. artikkel	1 stk
Vekt	0.2041165665 Kg
Inkludert i	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire
Tilleggsinfo	Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with

160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

**Delenummer konkurrenter** 22323 223-4148 6455 7-08752 71-276 9620 B1320040 T354-13 TU-4109

**Cross Sell** 165-015, 160-309, 165-021, 160-662, 160-003, 160-609, 160-300, 160-605, 160-633, 165-163, 160-344, 160-340

**Up Sell** Use with 165-015 Tire 165-015 Tire, Use with 160-309 Tire 160-309 Tire, Use with 165-021 Tire 165-021 Tire, Use with 160-662 Tire 160-662 Tire, Use with 160-003 Tire 160-003 Tire, Use with 160-609 Tire 160-609 Tire, Use with 160-300 Tire 160-300 Tire, Use with 160-605 Tire 160-605 Tire, Use with 160-633 Tire 160-633 Tire, Use with 165-163 Tire 165-163 Tire, Use with 160-344 Tire 160-344 Tire, Use with 160-340 Tire 160-340 Tire

**Produsentens merkevare** Stens

**GTIN-nummer** 023899091140

**Relatert produkt** 160-003

**OEM-nummer** Carlisle: 320040, 320160. Snapper: 1-0821, 7010821, 7010821YP

**Produsentinformasjon** Bruk med 160-003 Tire

**Lengde** 166.0 mm

**Høyde** 89.0 mm

**Bredde** 118.0 mm

**Vekt** 0.16 kg

Les mer om produktet her:

<https://www.ariens.no/product?number=170-138>