





**ΡίΓθαι** 13x6. 50-6



Smooth 4 Ply Tread: Smooth Tread Smooth Tire Size 13x6.50-6 Ply 4 Rim Size 6" Max PSI 28 Max Load Capacity 480 Type TubelessTire and wheel solutions for homeowner and grounds care professional applicationsThe smooth tire design allows optimum contact with various work surfaces for easy-flowing traction and a smooth rollAlso works smoothly as wide-flotation tires for on-site transportationProven rubber compounds and tread designs get the job done You may also like 160-016 Tire 160-016 Tire, Use with 170-175 Tube 170-175 Tube

Tread: Smooth Tread Smooth Tire Size 13x6.50-6 Ply 4 Rim Size 6" Max PSI 28 Max Load Capacity 480 Type TubelessTire and wheel solutions for homeowner and grounds care professional applicationsThe smooth tire design allows optimum contact with various work surfaces for easy-flowing traction and a smooth rollAlso works smoothly as wide-flotation tires for on-site transportationProven rubber compounds and tread designs get the job done

Stens	
Passer merke	Bobcat
Relatert produkt	160-016
Varegruppe	Tire
Antall pr. artikkel	1 stk
Vekt	2.5582609668 Kg
OEM-nr	Carlisle 512186;
Delenummer konkurrenter	0455121861 10290 222-9446 58-399 70-399 B1TI29 IM-8038 TI-29
Passer modell	Bobcat ZT200 Serial No. 942200-942299, 61" rider cutter decksExmark Lazer Z Serial No. 102,000-220,000 and Lazer Z Triton Serial No. 600,000 and newer; 52", 60" and 72" decksJohn Deere 737 and 757 Z-TrakScag Sabre Tooth Tiger, Tiger Cat, Tiger Cub, Turf Tiger and WildcatToro Z 500'S Z Master, 60" and 72" decks; Z250 Z Master 742XX Series, 52", 62" and 72" decks; 74260 Z 597, 60" and 72" decksWalker MT
Cross Sell	160-016, 170-175



Up Sell You may also like 160-016 Tire 160-016 Tire, Use with 170-175 Tube 170-175 Tube

Tilleggsinfo You may also like 160-016 Tire 160-016 Tire, Use with 170-175 Tube 170-175 Tube

Les mer om produktet her:

https://www.ariens.no/product?number=165-632